

ESD-wrist strap

Adjustable and elastic wrist strap without metal contact plate, anti-allergenic, snap fasteners 3 mm.

As accessory, there is a highly elastic helix cable (2.4 m) with 2x 1 MOhm electrical safety resistance.

Wrist strap connection

3 mm snap fastener

Connection to earth contact



Code No.	Type
WAC042000089	wrist strap
WAC042000090	helix cable 2,4 m

ESD-earthing box

Box as central earthing point connection (EBP-Earth Bonding Point) for personal grounding. Earth wire 2 m long. Mode of connection 4 mm eye-let bolt, per connection 1 MOhm safety resistance. 2x 10 mm snap fastener, 1x 4 mm safety bush.



Code No.	Type
WAC042000091	earthing box

ESD-central earthing connecting strip

Central connecting strip for the connection of maximal six earth wires with threaded terminals for cable lugs with 4 mm eyes.



Code No.	Type
WAC042000092	central earthing connecting strip

ESD-earth component

Dummy plugs for two-pin grounded plugs for direct earthing of table mats and floor covering or central earthing connecting strip.
With 2.4 m helix cable,
1 MOhm safety resistance,
10 mm snap fastener.



Code No.	Type
WAC042000094	2,0 m smooth cable
WAC042000093	2,4 m helix cable

ESD-earthing cable

Earthing cable for table /floor covering.
Smooth cable with 1 MOhm safety resistance,
10 mm snap fastener,
4 mm eyelet bolt



Code No.	Type
WAC042000095	1,5 m cable
WAC042000096	3,0 m cable